

SKIVED AND ROLLER BURNISHED CYLINDER TUBES H8

TUBI TRAFILATI PER CILINDRI PELORULLATI FINITI H8

EN 10305-2

TECHNICAL CHARACTERISTICS <i>Caratteristiche tecniche</i>	
GRADE QUALITÀ	E355
TREATMENT <i>TIPOLOGIA DI TRATTAMENTO</i>	+SR (BKS)
SURFACE FINISHING <i>FINITURA SUPERFICIALE</i>	<ul style="list-style-type: none"> • Outside diameter: smooth as drawn (EN 10305-2) <i>Diametro esterno: liscio e trafilato sec. EN 10305-2</i> • Inside diameter: skived and roller-burnished H8 Ra max 0.3 μ <i>Diametro interno: pelati e rullati H8 Ra max 0,3 μ</i>
DIMENSIONAL TOLERANCES <i>TOLLERANZE DIMENSIONALI</i>	<ul style="list-style-type: none"> • Insidel diameter: ISO H8, min. 40 mm - max. 220 mm <i>Diametro interno: ISO H8, min. 40 mm - max. 220 mm</i>

STANDARD DELIVERY PROGRAM

TABELLE DIMENSIONALI DEL PROGRAMMA DI FORNITURA STANDARD

weight kg/m

SKIVED AND ROLLER BURNISHED CYLINDER TUBES

Tubi trafilati per cilindri finiti internamente

inside Ø mm	outside Ø mm	wall thickness mm	weight kg/m
40,0	50,0	5,0	5,55
	52,0	6,0	6,81
	55,0	7,5	8,79
45,0	55,0	5,0	6,17
	57,0	6,0	7,55
	60,0	7,5	9,71
50,0	60,0	5,0	6,78
	62,0	6,0	8,29
	65,0	7,5	10,63
55,0	65,0	5,0	7,40
	67,0	6,0	9,03
	70,0	7,5	11,56
60,0	70,0	5,0	8,01
	72,0	6,0	9,77
	75,0	7,5	12,48
	80,0	10,0	17,26
63,0	73,0	5,0	8,38
	75,0	6,0	10,21
	78,0	7,5	13,04
	83,0	10,0	18,00
65,0	75,0	5,0	8,63
	77,0	6,0	10,51
	80,0	7,5	13,41
	85,0	10,0	18,50
70,0	80,0	5,0	9,25
	82,0	6,0	11,24
	85,0	7,5	14,33
	90,0	10,0	19,73
75,0	85,0	5,0	9,86
	87,0	6,0	11,98
	90,0	7,5	15,26
	95,0	10,0	20,96
80,0	90,0	5,0	10,48
	92,0	6,0	12,72
	95,0	7,5	16,18
	100,0	10,0	22,19

inside Ø mm	outside Ø mm	wall thickness mm	weight kg/m
85,0	95,0	5,0	11,10
	97,0	6,0	13,46
	100,0	7,5	17,11
90,0	105,0	10,0	23,43
	100,0	5,0	11,71
	102,0	6,0	14,20
	105,0	7,5	18,03
95,0	110,0	10,0	24,66
	105,0	5,0	12,33
	107,0	6,0	14,94
	110,0	7,5	18,96
100,0	115,0	10,0	25,89
	110,0	5,0	12,95
	112,0	6,0	15,68
	115,0	7,5	19,88
105,0	120,0	10,0	27,13
	115,0	5,0	13,56
	117,0	6,0	16,42
	120,0	7,5	20,81
110,0	125,0	10,0	28,36
	120,0	5,0	14,18
	122,0	6,0	17,16
	125,0	7,5	21,73
	130,0	10,0	29,59
	135,0	12,5	37,76
115,0	140,0	15,0	46,24
	125,0	5,0	14,80
	127,0	6,0	17,90
	130,0	7,5	22,66
	135,0	10,0	30,83
120,0	140,0	12,5	39,30
	145,0	15,0	48,09
	130,0	5,0	15,41
	132,0	6,0	18,64
	135,0	7,5	23,58
140,0	10,0	32,06	

inside Ø mm	outside Ø mm	wall thickness mm	weight kg/m
120,0	145,0	12,5	40,84
	150,0	15,0	49,94
125,0	135,0	5,0	16,03
	137,0	6,0	19,38
	140,0	7,5	24,51
	145,0	10,0	33,29
	150,0	12,5	42,38
	155,0	15,0	51,79
130,0	140,0	5,0	16,65
	142,0	6,0	20,12
	145,0	7,5	25,43
	150,0	10,0	34,52
	155,0	12,5	43,93
	160,0	15,0	53,64
135,0	145,0	5,0	17,26
	147,0	6,0	20,86
	150,0	7,5	26,36
	155,0	10,0	35,76
	160,0	12,5	45,47
	165,0	15,0	55,49
140,0	150,0	5,0	17,88
140,0	152,0	6,0	21,60
	155,0	7,5	27,28
	160,0	10,0	36,99
	165,0	12,5	47,01
145,0	170,0	15,0	57,33
	155,0	5,0	18,50
	157,0	6,0	22,34
	160,0	7,5	28,20
	165,0	10,0	38,22
170,0	12,5	48,55	
175,0	15,0	59,18	

inside Ø mm	outside Ø mm	wall thickness mm	weight kg/m
150,0	160,0	5,0	19,11
	162,0	6,0	23,08
	165,0	7,5	29,13
	170,0	10,0	39,46
160,0	175,0	12,5	50,09
	180,0	15,0	61,03
	170,0	5,0	20,34
	172,0	6,0	24,56
170,0	175,0	7,5	30,98
	180,0	10,0	41,92
	185,0	12,5	53,17
	190,0	15,0	64,73
180,0	185,0	7,5	32,83
	190,0	10,0	44,39
	195,0	12,5	56,26
	200,0	15,0	68,43
190,0	195,0	7,5	34,68
	200,0	10,0	46,85
	205,0	12,5	59,34
	210,0	15,0	72,13
200,0	205,0	7,5	36,53
	210,0	10,0	49,32
	215,0	12,5	62,42
	220,0	15,0	75,83
200,0	215,0	7,5	38,38
	220,0	10,0	51,79
	225,0	12,5	65,50
230,0	15,0	79,53	